

Through Beam Lightbarriers (Rectangular Sizes)

# EUHT 5207

**52 (PNP-NO+NC - programmable)**



|                          |                                          |
|--------------------------|------------------------------------------|
| Connection:              | 2 m cable                                |
| Connection type:         | cable                                    |
| Switching frequency:     | ≤ 1 ms                                   |
| Outlet:                  | PNP-NO+NC - programmable                 |
| Design:                  | 52                                       |
| Specialty:               | polarized, radial                        |
| Adjustment range:        | single turn potentiometer (20 %...100 %) |
| Function:                | trough beam lightbarrier                 |
| Case material:           | PBT                                      |
| Weight:                  | 120 g                                    |
| Short protection:        | yes, yes                                 |
| LED outlet + stability:  | orange, green                            |
| No-load current:         | ≤ 30 mA                                  |
| Light source:            | LED red                                  |
| Lens material:           | Methacrylic resin                        |
| Protection class:        | IP 67                                    |
| Voltage drop:            | ≤ 2 VDC                                  |
| Voltage range:           | 12...24 VDC                              |
| Ampacity:                | ≤ 100 mA                                 |
| Tap range:               | 0... 10 m                                |
| Environment temperature: | -25 °C ...+55°C                          |

Further information about this product can be found on our website, please visit:  
[https://schoenbuch-sensor.de/en/products/euht-5206\\_en/euht-5207\\_en/](https://schoenbuch-sensor.de/en/products/euht-5206_en/euht-5207_en/)