


# INHV5512

## R55 (NPN NO)



|                          |                                  |
|--------------------------|----------------------------------|
| Connection:              | 2 m PVC/3 x 0,14 mm <sup>2</sup> |
| Connection type:         | cable                            |
| Outlet:                  | NPN NO                           |
| Design:                  | R55 (5x5x26)                     |
| Width:                   | 5,5 mm                           |
| Installation type:       | non flush                        |
| Height:                  | 5,5 mm                           |
| Short protection:        | yes                              |
| Length:                  | 19 mm                            |
| LED:                     | yes                              |
| No-load current:         | 15 mA                            |
| Nominal voltage:         | 24 VDC                           |
| Reproducibility:         | 1 %                              |
| Switching distance:      | 1,6 mm                           |
| Switching frequency:     | 1000 Hz                          |
| Switching hysteresis:    | 15 %                             |
| Protection class:        | IP 67                            |
| Voltage drop:            | 1 V                              |
| Voltage type:            | VDC                              |
| Voltage range:           | 10 - 30 V                        |
| Ampacity:                | 50 mA                            |
| Temperature drift:       | 10 °C                            |
| Environment temperature: | -25 bis 70 °C                    |
| Material:                | plastic                          |

Further information about this product can be found on our website, please visit:

[https://schoenbuch-sensor.de/en/products/inhv5514\\_en/inhv5512\\_en/](https://schoenbuch-sensor.de/en/products/inhv5514_en/inhv5512_en/)