

Reflective Types (Rectangular Sizes)

TCRI 6001

60 (Analog Ausgang)



| | |
|-------------------------------|--|
| Analog outlet: | 0...10 V/resolution 1mm (linearity ±2,5 %) |
| Connection: | plug M12 |
| Connection type: | plug M12 |
| Switching frequency: | 500 µs, 1 kHz |
| Outlet: | Analog Ausgang |
| Design: | 60 |
| Specialty: | Laser |
| Adjustment range: | Teach in |
| EMC: | EN 60947-5-2 |
| Function: | reflective type |
| Case material: | ABS |
| Short protection: | yes, yes |
| LED outlet + stability: | yellow, green, red |
| No-load current: | ≤ 40 mA |
| Light source: | LED red |
| Lens material: | PMMA |
| Switching distance frequency: | Kodakcard white 10 x 10 mm |
| Switching hysteresis: | ≤ 20 % [Sn] |
| Protection class: | IP 67 |
| Voltage drop: | ≤ 2 VDC |
| Voltage range: | 10... 30 VDC |
| Ampacity: | ≤ 100 mA |
| Tap range: | 50...150 mm |
| Environment temperature: | -25 °C ...+55°C |
| VDE protection class: | class 2 |

Further information about this product can be found on our website, please visit:
https://schoenbuch-sensor.de/en/products/tcht-6001_en/tcri-6001_en/