
Accessoires (Distributor)

# ZVHK 230810

## Distributor M12 IDC Quick Connection (8-fach/3-pin/Kabel 10m)




| | |
|---|---|
| Conductor diameter: | 1,2 - 1,6mm |
| Conductor slice plane: | 0,25 - 0,5 $mm^2$ |
| Slot qty.: | 4/8 |
| Base material contacts: | CuZn, nickeling and gold plated |
| Nominal voltage: | 30V |
| EA function: | 1x LED yellow |
| Color: | black |
| Case sealing: | PUR foaming |
| Total: | 8A |
| Screw socket: | CuZn, nickeling |
| Insulation material case: | PBT (UL 9400) |
| Cable coat: | PUR |
| Contact beam: | PBT (UL 9400) |
| Conductor outer diameter: | 3,5 - 0,5mm |
| Max. connection frequency: | 10 |
| Max. currency per E.-outlet: | 2A |
| Min. cord diameter: | 0,1mm |
| Minimum skinning length: | 15...20mm |
| O-ring: | viton |
| PG and contact mount: | black |
| Number of poles: | 3/4 |
| Protection class: | IP 68 |
| UB: | 1x LED green |
| Environment temperature: | -20 °C ... +90 °C |
| Fouling level: | 3 |

Further information about this product can be found on our website, please visit:
**https://schoenbuch-sensor.de/en/products/zvhh-2304_en/zvhk-230810_en/**